

P1 1177308

REC'D 03 JUN 2004

WIPO

PCT

THE UNITED STATES OF AMERICA

TO ALL TO WHOM THESE PRESENTS SHALL COME:

UNITED STATES DEPARTMENT OF COMMERCE
United States Patent and Trademark Office

May 28, 2004

THIS IS TO CERTIFY THAT ANNEXED HERETO IS A TRUE COPY FROM THE RECORDS OF THE UNITED STATES PATENT AND TRADEMARK OFFICE OF THOSE PAPERS OF THE BELOW IDENTIFIED PATENT APPLICATION THAT MET THE REQUIREMENTS TO BE GRANTED A FILING DATE.

APPLICATION NUMBER: 60/458,489

FILING DATE: March 28, 2003

RELATED PCT APPLICATION NUMBER: PCT/US04/09610

By Authority of the
COMMISSIONER OF PATENTS AND TRADEMARKS



H. L. Jackson
H. L. JACKSON
Certifying Officer

PRIORITY DOCUMENT
SUBMITTED OR TRANSMITTED IN
COMPLIANCE WITH
RULE 17.1(a) OR (b)

BEST AVAILABLE COPY

3-340036489-052804/170

Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE

PROVISIONAL APPLICATION COVER SHEET

This is a request for filing a PROVISIONAL APPLICATION under 37 CFR 1.53(c).

DOCKET NUMBER: B01075.70039
Express Mail Label No. EV 208 517 799 US
Date of Deposit: March 28, 2003

1-979 U.S. PTO
60/458489
03/28/03

INVENTOR(S)/APPLICANT(S)

LAST NAME	FIRST NAME	MIDDLE INITIAL	RESIDENCE (CITY AND EITHER STATE OR FOREIGN COUNTRY)
Stevens-Wright Sagon	Debbie Stephen	W.	North Andover, MA Amherst, NH

☐ Additional inventors are being named on the separately numbered sheets attached hereto.

TITLE OF THE INVENTION (280 characters max)

ELECTRODE FOR ELECTROPHYSIOLOGY CATHETER HAVING AN ECCENTRIC SURFACE

CORRESPONDENCE ADDRESS

CUSTOMER NUMBER:

23628

ENCLOSED APPLICATION PARTS (check all that apply)

- ☒ Specification - Number of Pages = 8
- ☐ Drawing(s) - Number of Sheets
- ☐ Application Data Sheet, See 37 CFR 1.76
- ☒ Return receipt postcard

The invention was made by an agency of the United States Government or under a contract with an agency of the United States Government.

☒ No
☐ Yes, the name of the U.S., Government Agency and the Government Contract Number are:

☐ Other:


METHOD OF PAYMENT (check all that apply)

- ☒ A check is enclosed to cover the Provisional Filing Fees.
- ☐ The Commissioner is hereby authorized to charge any additional fees or credit overpayment to Deposit Account 23/2825. A duplicate of this sheet is enclosed.
- ☐ Small Entity Status is claimed.

PROVISIONAL FILING FEE AMOUNT \$ 160.00


March 28, 2003
Date

Respectfully submitted,


James H. Morris, Reg. No. 34,681
Telephone No.: 617-720-3500

Description of Eccentric Electrode

The "Eccentric Electrode Design" has a large tissue contact surface area. This surface area is larger than the blood contact surface area of the electrode. The objective of the larger tissue contact surface area is to produce deeper ablation lesions. In addition the electrode will minimize the mass in contact with the blood. The smaller mass will assure that minimal heating occurs along the blood contact surface. Two embodiments of the design are shown below.



60458489.032803



111
TITLE Eccentric Electrode

From Page No. _____


Description of Eccentric Electrode

The "Eccentric Electrode Design" has a large tissue contact surface area. This surface area is larger than the blood contact surface area of the electrode. The objective of the larger tissue contact surface area is to produce deeper ablation lesions. In addition the electrode will minimize the mass in contact with the blood. The smaller mass will assure that minimal heating occurs along the blood contact surface. Two embodiments of the design are shown below.

William E. Stern-Wright*William E. Stern-Wright*To Page No. 2

TITLE *Eccentric Electrode*

From Page No. _____




Adrian B. Stenerson-Wright

TITLE *Eccent*

From Page No. _____

TITLE *Eccentric Electrode*

From Page No. _____



Alpha E. Williams - Wright

To Page No. 3


To Page No. _____

TITLE Eccentric Electrode Design

111

From Page No. _____

Analysis of eccentric electrode design shows that the convective flow across the tissue surface is improved with this design. This design helps to lift the catheter tubing away from tissue surface, thus improving blood flow across the tissue surface. This cooling allows more energy to be transferred into the tissue before reaching the maximum tissue temperature of 100°C . The chart below shows the relative improvement that this design offers over various other designs. The diagram below shows the offset for a 9F, 4mm electrode design.



To Page No. _____

||||
TITLE Eccentric Electrode Design


From Page No. _____

Temperature and Velocity Profiles

9F Can Guppy 4mm - Temperature and Velocity Profiles




30 mm/sec 25V



55 mm/sec 25V




85 mm/sec 25V




30 mm/sec 35V



55 mm/sec 35V



85 mm/sec 35V



30 mm/sec 45V



55 mm/sec 45V



85 mm/sec 45V

Dibble & Steven Weigh

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

☐ BLACK BORDERS

☒ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES

☐ FADED TEXT OR DRAWING

☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING

☐ SKEWED/SLANTED IMAGES

☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS

☐ GRAY SCALE DOCUMENTS

☐ LINES OR MARKS ON ORIGINAL DOCUMENT

☒ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY

☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.